

# BJM CORP.

123 Spencer Plains Road,  
P.O. BOX 1138, Old Saybrook, CT 06475, USA  
(860) 399-5937 · (800) 442-2562 · Fax: (860) 399-7784  
Visit our web site: [www.bjmcop.com](http://www.bjmcop.com)

10/30/2002

0802

Supersedes

0801

## TECHNICAL DATA MODEL J55CH BJM SUBMERSIBLE PUMP-CAST IRON

### GENERAL DATA

MAX. FLOW: GPM (L/min)	274 GPM (1037 L/min)
MAX. HEAD: ft (m)	117' (35.6 m)
PUMP TYPE	DEWATERING
STRAINER OPENING	0.375" (9.5 mm) diameter
IMPELLER DIAMETER: in (mm)	6.14" (156 mm)
DISCHARGE SIZE	3" NPT FEMALE
PUMP NET WEIGHT <sup>1</sup> : lbs (kg)	170 lbs (77.3 kg)
SHIPPING WEIGHT: lbs (kg)	205 lbs (93.2 kg)

1- Does not include power cord.

### CONSTRUCTION/MATERIAL DATA

MECHANICAL SEAL - UPPER	CARBON/CERAMIC
MECHANICAL SEAL - LOWER	SILICON CARBIDE/SILICON CARBIDE
MOTOR CASING	304 SS
PUMP VOLUTE	CAST IRON
IMPELLER- MULTI VANE	CAST IRON
STRAINER	STEEL
LIPSEAL & O-RINGS	BUNA-N
ROTOR SHAFT	304 SS
EXTERNAL HARDWARE	304 SS
QTY. OIL IN SEAL CHAMBER	27 U.S. FL. OZ. (800 C.C.)
BALL BEARING: PERM. LUBE. UPPER	6305
BALL BEARING: PERM. LUBE. LOWER	6207 (x2)

### ELECTRICAL /MOTOR DATA

MOTOR: TYPE, RATING HP	SUBMERSIBLE, 7.5
MOTOR RPM	3450
MOTOR INSULATION CLASS	F
MOTOR SERVICE FACTOR	1.1
VOLTAGE <sup>2</sup>	230/460, 3 PH, 60 Hz ; OPTION 208V/3PH/60Hz
CURRENT F.L.A. AT 230/460 V	21/10.5
MOTOR PROTECTION	THERMAL & AMP. OVERLOAD
POWER CORD <sup>3</sup> : GAGE; LENGTH	A.W.G. 10/4; 33' (10 m)
MAXIMUM LIQUID TEMPERATURE	104°F (40°C)
MAXIMUM STATOR TEMPERATURE	230°F (110°C)
SEAL LEAK DETECTOR <sup>4</sup> (OPTIONAL)	SEAL MINDER; MOISTURE SENSING PROBE


2- Available in other voltages (and in 50 Hz).

3- Available in 5 leads cable(3 phase power only) and different length.

4- Requires a circuit in control panel for warning signal.

REFER TO REVERSE SIDE FOR PUMP PERFORMANCE CURVES  
SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

# MODEL: J55CH



MOTOR: 7.5 HP  
SPEED: 3450 RPM  
VOLTAGE: 230/460 VOLT, 60 Hz, 3 PH  
IMPELLER: 6.14" DIA.  
DISCHARGE SIZE: 3" NPT FEMALE

12/30/2002 supersedes priors

FLOW RATE PER MINUTE

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE