

BJM CORP.

123 Spencer Plains Road,
P.O. BOX 1138, Old Saybrook, CT 06475, USA
(860) 399-5937 · (800) 442-2562 · Fax: (860) 399-7784
Visit our web site: www.bjmcop.com

3/31/2003
0803
Supersedes
0802

TECHNICAL DATA MODEL R400 BJM SUBMERSIBLE PUMP-CAST IRON



GENERAL DATA

MAX. FLOW: GPM (L/min)	66 GPM (249 L/min)
MAX. HEAD: ft (m)	35' (10.6 m)
PUMP TYPE	TOP DISCHARGE, DEWATERING
STRAINER OPENING	0.1875" (4.7 mm)
IMPELLER DIAMETER: in (mm)	3.75" (95 mm)
DISCHARGE SIZE	2" NPT-MALE
PUMP NET WEIGHT ¹ : lbs (kg)	29 lbs (13.2 kg)
SHIPPING WEIGHT: lbs (kg)	33 lbs (15 kg)

1- Does not include power cord.

CONSTRUCTION/MATERIAL DATA

MECHANICAL SEAL - UPPER	CARBON/CERAMIC
MECHANICAL SEAL - LOWER	SILICON CARBIDE/SILICON CARBIDE
OUTER CASING	304 SS
MOTOR CASING	304 SS
PUMP VOLUTE	CAST IRON
IMPELLER- MULTI VANE	CAST IRON
STRAINER	304 SS
BOTTOM PLATE	RUBBER COATED CAST IRON
LIPSEAL & O-RINGS	BUNA-N
ROTOR SHAFT	304 SS
EXTERNAL HARDWARE	304 SS
QTY. OIL IN SEAL CHAMBER	1.35 U.S. FL. OZ. (40 C.C.)
BALL BEARING: PERM. LUBE. UPPER	6201
BALL BEARING: PERM. LUBE. LOWER	6201

ELECTRICAL /MOTOR DATA


MOTOR: TYPE, RATING HP	SUBMERSIBLE, 0.5
MOTOR RPM	3450
MOTOR INSULATION CLASS	F
MOTOR SERVICE FACTOR	1.1
VOLTAGE ²	115, 1 PH, 60 Hz
CURRENT F.L.A.	6
MOTOR PROTECTION	THERMAL BREAKER
POWER CORD ³ : GAGE; LENGTH	A.W.G. 16/3; 33' (10 m)
MAXIMUM LIQUID TEMPERATURE	104°F (40°C)
MAXIMUM STATOR TEMPERATURE	230°F (110°C)

2- Available in other voltages (and in 50 Hz).

3- Available in different length.

REFER TO REVERSE SIDE FOR PUMP PERFORMANCE CURVES
SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

MODEL: R400



12/30/2002 supersedes priors

FLOW RATE PER MINUTE

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE